


Sydney Bathroom Hire

Dual Deluxe Toilet Requirements Check List

There are some important factors that you need to consider before hiring one of our dual deluxe toilets.

Please read the following requirements carefully.

- **Suitable access is required.** The bathroom requires **2400mm width access** and **2800mm height access**. We require 3.200m in clear height to remove the toilet unit from the trailer. Make sure it will fit where you want it to go. **Remember to include the tow vehicle and don't forget roof eaves, pipes, air conditioning systems, trees and shrubs and other obstructions.** Don't forget deep driveway gutters. Email photos of site and access if you are unsure. **Please have all plants trimmed and obstacles removed before delivery.**
- **If we can not install on delivery due to unsuitable access or services you may forfeit your whole hire payment.** A pre-hire inspection can be arranged and charges will apply. **Our representatives are good drivers but are not precision stunt drivers. We will not risk damaging our bathrooms.**
- **Electricity** is standard **10 AMP/ 240 volts power supply**. The dual toilet unit requires **one power point**. Please ensure the power point is in good condition. **We supply 30 metre leads tagged and tested for your safety.** No power boards can be used. A generator of 5.5 KVA is sufficient for remote locations.
- **Water** needs to be connected so a tap is required. Preferably a garden tap under mains or pump pressure. **We will supply the tap connection and 20 metres of AS2070 drinking quality hose.** Extra hose can be supplied at your request. **Check to see if your tap leaks when turned on.**
- **Sullage** is discharged through a **32mm flexible hose** pumped automatically into your existing sewer via your overflow relief gully, inspection opening, or similar access point (see picture). **Inspect your outside sewer system for a suitable opening.** If in doubt please contact your local plumber or arrange a pre-hire inspection. Septic tanks and envirocycle type systems are fine. We supply all necessary hoses and connections. **Please advise us if the distance to sewer services is greater than 20 metres. Maximum distance is 50 metres with a one metre rise.**
- Ground must be **reasonably level**. If the site is not level please inform us. The front of the dual toilet unit preferably should be at the highest point.
- If you **supply labour** to manoeuvre the dual toilet unit into place by hand then the **same labour must be provided on pick up or you may be charged extra.**
- Payment is required in full to secure your booking. If you cancel outside of 4 weeks you will get a full refund. If not you will receive a percentage refund. No refunds are given if cancelled within 7 days. A condition report will be completed with you on delivery.
- **Toilets must be cleaned out before pick up. Excessive dirt and grime will attract a cleaning fee dependant on time required to return the toilets to the same condition it was in when handed over to you.**



“For all your portable bathroom solutions”